

CENTENNIAL 25

HIGH SOLIDS FLOOR FINISH

DESCRIPTION:

CENTENNIAL 25 is a high-solids non-buff metal cross-linked floor finish which combines high gloss with excellent durability. CENTENNIAL 25 is an exceptional topcoat for SEAL-A-TEX II on cement floors in warehouses subjected to forklift traffic. CENTENNIAL 25 dries to a uniform clear film and provides exceptional response to high speed buffing with or without the use of spray buffs.

UL LISTING:



Floor Coating and Finishing Material as to Slip Resistance Only – 217S

TOTAL SOLIDS:

23 % Minimum

FOR USE ON:

Resilient Tile, Linoleum, Terrazzo, Marble, Concrete, Sealed Cork, and Sealed Wood Floors.

DIRECTIONS:

Preparation: If floor is clean and coated with a non-buff floor finish, stripping prior to application, although recommended for best results, is not required.

Application: On a newly stripped floor, 3 base coats are recommended. Apply product with string mop or other suitable applicator. Under normal conditions, only 30 minutes dry time between coats is required. If weather is very humid or damp, longer dry times may be necessary.

Maintenance: Periodic cleaning with dilute solutions of SANOVER or TUFFKLEEN and occasional spray-buffing with RESTOR-A-FLOOR will maintain the gloss and appearance of CENTENNIAL 25 and will minimize the need for recoating.

REMOVABILITY:

When stripping does become necessary, this may be accomplished easily with TUFF-STRIP 911, non-ammoniated SANISTRIP XL or H.D. STRIPPER.

HEALTH & SAFETY:

CAUTION:

DO NOT TAKE INTERNALLY — AVOID EYE AND SKIN CONTACT

— FIRST AID —

If Accidentally Swallowed, give milk or water to drink. Call physician.

Eye or Skin Contact, flush affected area with water for 15 minutes. Call physician if irritation persists.

This product is registered with the Local Poison Control Center.

For Industrial and Institutional Use Only

KEEP OUT OF REACH OF CHILDREN

Do Not Store in Open or Unmarked Containers

See Product MSDS for more Health & Safety Information.

COVERAGE:

One gallon will cover from 1800-2200 square feet depending upon the condition and porosity of the floor.

PACKAGING:

4/1 gallon case, 5-gallon pails, and 55-gallon drums.

ITEM NO.:

010

07/98



SANITEK

CHEMICAL SPECIALTIES MANUFACTURER

Sanitek Products, Inc. • 3959 Goodwin Ave., Los Angeles, CA 90039 • Phone (323) 245-6781