

DESCRIPTION:

STAR is a high-solids, high-gloss floor finish that has exceptional durability. May be used in high-speed or ultra-speed maintenance programs. Manufactured from the newest generation of high-molecular weight acrylic polymers and thermoplastic resins, the STAR system provides superior cost savings when compared to other high-speed floor finish systems.

ADVANTAGES:

- Reduce Labor Costs; Only 2-3 Coats Required For Excellent Gloss
- Optimum Floor Finish System When Used With Hold-Out Sealer
- Enhanced Gloss & Performance With 1000+ RPM Buffers

UL LISTING:



Floor Coating and Finishing Material as to Slip Resistance Only – 217S

TOTAL SOLIDS:

24% Minimum

FOR USE ON:

Resilient Tile, Linoleum, Terrazzo, Marble, Concrete, Sealed Cork, and Sealed Wood Floors.

DIRECTIONS:

Preparation: If floor is clean and coated with a non-buff floor finish, stripping prior to application is not required.

Application: On a newly stripped floor, 1-2 coats of Seal-a-Tex II or Hold-Out floor sealer is recommended. On a sealed floor, 2-3 coats of STAR floor finish are recommended. Apply product with clean string mop or other suitable applicator. Under normal conditions, allow 30 minutes dry time between coats. If weather is very humid or damp, longer dry times may be necessary. Allow 24 hours; then buff to maximum gloss with a suitable pad using a 1000+ rpm burnisher.

Maintenance: Periodically clean with dilute solutions of Tuffkleen. Although not required for excellent gloss, spray-buffing with Restor-a-Floor or Cristal Clear Spray Buff will further enhance the gloss and appearance of STAR and will minimize the need for recoating.

REMOVABILITY:

When stripping does become necessary, this may be accomplished easily with ammoniated Tuff-Strip 911, non-ammoniated Sanistrip XL, or H.D. Stripper.

HEALTH & SAFETY:

CAUTION: DO NOT TAKE INTERNALLY — AVOID EYE AND SKIN CONTACT

— FIRST AID —

If Swallowed: give milk or water to drink. Call physician.

Eye or Skin Contact: flush affected area with water for 15 minutes. Call physician if irritation persists.

For Industrial and Institutional Use Only

KEEP OUT OF REACH OF CHILDREN

Do Not Store in Open or Unmarked Containers

See Product MSDS for more Health & Safety Information.

COVERAGE:

One gallon will cover from 1500-2000 square feet depending upon the application rate and the condition and porosity of the floor.

PACKAGING:

4/1 gallon case, 5-gallon pails, and 55-gallon drums.

ITEM NO.:

018

07/98



SANITEK

CHEMICAL SPECIALTIES MANUFACTURER

Sanitek Products, Inc. • 3959 Goodwin Ave., Los Angeles, CA 90039 • Phone (323) 245-6781