

**DESCRIPTION:**

TUFFSHEEN offers the optimum balance of properties in a floor wax: lustre, buffability, durability, water-resistance, and slip resistance. TUFFSHEEN is extremely resistant to powdering and black heel marking. TUFFSHEEN can be buffed to restore original lustre.

**TOTAL SOLIDS:**

16% Minimum.

**UL LISTING:**

Classified by Underwriters Laboratories Inc. as to Slip Resistance Only – 217S

**FOR USE ON:**

Resilient tile, linoleum, terrazzo, marble, concrete, sealed cork, and sealed wood floors. NOT RECOMMENDED FOR OUTSIDE USE.

**DIRECTIONS:**

For best results, it is IMPORTANT that the floor be cleaned thoroughly before applying wax.

**Preparation:** If floor is clean and coated with a non-buff floor finish, stripping prior to application, although recommended for best results, is not required.

**Application:** On a newly stripped floor, 2 base coats are recommended. Apply TUFFSHEEN with string mop or other suitable applicator. Under normal conditions, one hour dry time between coats is required. TUFFSHEEN can be buffed immediately after each coat is dry.

**Maintenance:** Periodic cleaning with dilute solutions of Sani-Banana or Tuffkleen and occasional spray-buffing with Restor-A-Floor will maintain the gloss and appearance of TUFFSHEEN and will minimize the need for recoating. DO NOT POUR USED MATERIAL BACK INTO CONTAINER.

**REMOVABILITY:**

When stripping does become necessary, this may be accomplished easily with Tuff-Strip 911, non-ammoniated Sanistrip XL, or H.D. Stripper. Call our Technical Service Department for special problems.

**HEALTH & SAFETY:****CAUTION:**

DO NOT TAKE INTERNALLY — AVOID CONTACT WITH EYES

— FIRST AID —

If **swallowed**, give milk or water to drink. Call physician.

**Eye or Skin Contact**, flush affected area with water for 15 minutes. Call physician if irritation persists.

This product is registered with the Local Poison Control Center.

For Industrial and Institutional Use Only

KEEP OUT OF REACH OF CHILDREN

Do Not Store in Open or Unmarked Containers

See Product MSDS for more Health & Safety Information

**COVERAGE:**

One gallon will cover from 1800-2200 square feet depending upon the condition and porosity of the floor.

**PACKAGING:**

4/1-gallon case, 5-gallon pails, and 55-gallon drums.

**ITEM NO.:**

070

04/98



**ANITEK**

CHEMICAL SPECIALTIES MANUFACTURER

Sanitek Products, Inc. • 3959 Goodwin Ave., Los Angeles, CA 90039 • Phone (323) 245-6781